


# OptiSafe® Surfacing Tape

## Blue Surface Saver Tape


4" x 36 yd/Roll (10 cm x 32.92 m)  
 Surface saver tape for Alloy blocking of lenses. Protects lenses against scratches and contamination. De-blocks cleanly and easily. Blue colored tape. Lens markings are completely visible.

Item #P1641



4" x 108 yd/Roll (10 cm x 98.76 m) (for Auto-taper)  
 Surface saver tape for Alloy blocking of lenses. Roll is 108 yds in length designed for the Auto-Taper. Protects lenses against scratches and contamination. Deblocks cleanly and easily. Blue colored tape. Lens markings are completely visible.

Item #P4327




Clear Surface Tape 4" x 72 yd/Roll (10 cm x 65.84 m) (linerless tape for wax blocking)  
 Surface saver tape for Non-Alloy (wax) blocking of lenses. Protects lenses against scratches and contamination. Deblocks cleanly and easily. Clear protective tape. Lens markings are completely visible.

Item # P1663



## 3M Surfacing Tape

### Alloy Blocking




**At 50 yards per roll, surface saver plus tape has 25%-39% more tape per roll** (shown by dotted line) than most competitive brands. That means you'll surface between 100 to 140 more lenses per roll before change-out\*. Whether you purchase 12-roll or 6-roll cases, you're assured of consistent quality time and time again.

\*Based on 10 - 3" (7.62cm) diameter lenses per yard.

Product Number	Alloy Blocking
1640	Higher
1641	Medium
1642	Light

### Wax Blocking



Only 3M 1663 Clear Protective Tape is specially designed to optimize your non-alloy (wax) blocking system. It protects against scratches and contamination, prevents cross-contamination and equipment damage, and promotes coating uniformity and adhesion. This amazing blocking tape is so clear, the lens markings are completely visible—making blocking alignment a snap. It bonds beautifully to wax to prevent fall-offs, yet de-blocks cleanly and easily every time.

Product Number	Non-Alloy Wax Blocking
1663	<b>Clear Protective Tape</b> —keep lens surface free of contaminants, like wax and oil, for problem-free AR adhesion.



PH-P1641-0808

**(800) 225-5559 U.S.A.**  
 +1-619-449-7754 International

[www.phantomresearch.com](http://www.phantomresearch.com)  
 email: [sales@phantomresearch.com](mailto:sales@phantomresearch.com)